

Cables Serie 8000 vrs THHN/THWN

CALIBRE THW	CALIBRE XHHW-2	AMPERES THW	AMPERES XHHW-2	DIAMETRO EXTERIOR THW MM	DIAMETRO EXT. XHHW-2 MM	KG/100 MTS THW	KG/100 MTS XHHW-2
8	6	50	50	6.0	6.6	10.3	5.9
6	4	65	65	7.8	7.7	16.6	8.6
4	2	85	90	9.0	9.1	24.9	12.7
2	1/0	115	120	10.5	11.4	34.5	20.0
	2/0		135		12.4		24.4
1/0	3/0	150	155	13.6	13.7	59.9	30.0
2/0	4/0	175	180	14.8	15.0	73.8	37.0
3/0	250	200	205	16.1	16.6	91.4	44.2
4/0	300	230	230	17.6	17.9	113.2	52.1
250	350	255	250	19.5	19.1	134.8	60.0
	400		270		20.2		67.9
300		285		20.9		159.7	
350	500	310	310	22.2	22.1	184.5	83.3
400	600	335	340	23.4	24.9	209.1	101.7
500	750	380	385	25.6	27.3	258.2	124.8
600	1000	420	445	28.3	31.1	319.5	163.5



VIKON
CONDUCTORES MONTERREY

8000